

# LX2084 • 120/277V • XICATO 19MM



**Remote phosphor technology produces high quality, high output light with a consistent, even field for the most demanding applications of museum and retail accent lighting.**


- Designed for the most versatile Xicato XTM 19mm LED module up to 56 Watts
- Extremely tight color consistency (less than 2 MacAdam Ellipses)
- System efficiency up to 70 lumens/watt
- Backed by Xicato's Five Year Color Consistency and Lumen Maintenance Warranty
- 50,000 hour life to 70% lumen output, L70 at 95°F max ambient
- Choice of color temperature
- Color Rendering Index (CRI) of either 98 (high) or 83+ (standard)
- Choice of lumen outputs (delivered lumens)
- Tested to LM79 and LM80 Protocols, TM-30 available
- Hidden integral electronic driver compatible with various dimmers down to 0.1%
- Integral dimmer available
- Lutron EcoSystem compatible with dimming to 1% (Lutron Hi-Lume Premier 1% EcoSystem LED Driver)
- Lutron EcoSystem features soft-on, fade to black, smooth flicker-free dimming from 0-100% (Meets IEEE 1789 for flicker)
- Field interchangeable optics (10°- 40°) modify the beam spread distribution
- Integral polycarbonate accessory cartridge accepts up to three size-C LSI filters and accessories
- Finishes: LSI Black, White, and Silver
- Fixture weight: 8 lbs
- All modules are field replaceable

## FIXTURE PART NUMBERS

Please review the **ORDERING INFORMATION** section on the next page as well as the **MOUNTING OPTIONS** on page 3 to create a part number for each fixture that specifies the following:


- LED Module
- LED Rating
- Color Temperature
- Optic - mm/beam spread
- Fitting/Controls (Dimming)
- Voltage
- Finish

### PART NUMBER



Example Part Number: **LX2084-T1930-9830K1-00-TE120W** is a fixture with a Xicato 19mm LED module, 3000 Lumen/98 CRI/41 Watt LED rating, 3000K Color Temperature, 111mm 10° Optic, 00 Track fitting with Trailing Edge group dimming capability, 120V and a White finish.

# LX2084 • 120/277V • XICATO 19MM



## Color Temperature & Center Point Tolerance

Color Temp	Center Point	Tolerance
2700K	2700K	+/- 40K
3000K	2950K	+/- 50K
3500K	3420K	+/- 60K
4000K	4000K	+/- 70K

## Chromaticity Specifications

LED	R <sub>a</sub> -CRI	R <sub>f</sub> -Fidelity	R <sub>g</sub> -Gamut Area
T19-TS9 - 83	83	78	101
T19-TS9 - 98	98	96	103

## XTM 19MM ORDERING INFORMATION

### Base Fixture Model

☐ LX2084-T19 (XTM 19mm)

### LED Rating (Lumens/CRI/Wattage)

☐ 20-83 = 2000/83/21    ☐ 20-98 = 2000/98/28  
☐ 30-83 = 3000/83/32    ☐ 30-98 = 3000/98/41  
☐ 40-83 = 4000/83/47    ☐ 50-83 = 5000/83/56

### Color Temperature

☐ 27 = 2700K    ☐ 30 = 3000K  
☐ 35 = 3500K    ☐ 40 = 4000K

### Optic

☐ K1 = 111mm/ 10°    ☐ W2 = 72mm/ 20°  
☐ J3 = 111mm/ 30°    ☐ W4 = 72mm/ 40°

### Fitting/Controls (Dimming)

☐ 00-TE = Track Fitting & Trailing Edge (5%)  
☐ 0D-ED = Track Fitting with Integral Dimmer (0.1%)  
☐ 00EF-TE = Security/Worklight Track Fitting & Trailing Edge (5%)  
☐ 2G-TE = Universal Fitting & Trailing Edge (5%)  
☐ 3G-TE = Pipe Clamp Fitting & Trailing Edge (5%)  
☐ 5A-TE = Canopy Fitting & Trailing Edge (5%)  
☐ 5A-ED = Canopy Fitting with Integral Dimmer (0.1%)  
☐ 5A-10 = Canopy Fitting & 0-10V (0.1%)  
☐ 5A-L3 = Canopy Fitting & Lutron EcoSystem (1% Soft On/Off)

**Coiled Cord** is available only with **2G** and **3G** mounting options. Change 2G to **2C** and 3G to **3C**. (When a coiled cord is not specified, a straight cord is provided.)

### Voltage

☐ 120 = 120V    ☐ 230 = 220-240V    ☐ 277 = 277V

### Finish

☐ B = Black    ☐ W = White    ☐ S = Silver













### Example Part Number:

**LX2084-T19**    **30-98**    **30**    **K1** - **00-TE**    **120**    **W**  
FIXTURE MODEL    LED RATING    COLOR TEMP    OPTIC    FITTING/DIMMING    VOLTAGE    FINISH

### Other Options (Consult Factory):

- Custom Stems, specify length (4" - 6")
- Custom color, RAL palette

# LX2084 • MOUNTING OPTIONS

FITTING	SIDE VIEW	STEM LENGTH VIEW
<b>00 Track Fitting/ 00EF Security/Worklight Fitting</b>		
<b>0D-ED Track Fitting with Integral Dimmer</b>		
<b>2G Universal Fitting</b>		
<b>3G Pipe Clamp Fitting</b>		
<b>5A Canopy Fitting with TE, 0-10V, &amp; L3 Dimming</b>		
<b>5A-ED Canopy Fitting with Integral Dimmer</b>		

# LX2084 • PERFORMANCE

The performance characteristics of the LumeLEX family of products can be customized based on the LED module and the optic (reflector) selected. Each available LED module is defined by four characteristics – the color rendering index (CRI), the correlated color temperature (CCT), the power that it uses (watts), and its “available lumens.” Note that available lumens is a theoretical value that represents the light output of the module on its own – no fixture or optic attached.

In the LSI part number, the LED module is specified with a letter and a number that immediately follow the product series number.

For example, in the part number LX2084-T1920-8327K1-00-TE120B, the “**T1920-8327**” represents an LED module with an output of 2000 lumens, a CRI of 83, a power usage of 21 watts and a color temperature of 2700K.

The available optics (reflectors) are characterized by size, beam angle, and in some cases the characteristics of the field angle (narrow or wide). The optic is specified by the two characters that follow the LED designation in the part number. For example, the “**K1**” in LX2084-T1920-8327K1-00-TE120B is a 111mm diameter optic that has a 10-Degree beam.

Additional parameters, such as Center Beam Candle Power (CBCP), Delivered Lumens, and Efficiency (Lumens per Watt) are all shown in a table that is organized by LED module and optic combination.

## CBCP = Center Beam Candle Power

LED Module	Optic (Reflector)			
Lumens/CRI/Wattage	K1	W2	J3	W4
2000/83/21	11,316	6,830	4,030	2,780
2000/98/28	11,316	6,830	4,030	2,780
3000/83/32	16,974	10,245	6,044	4,170
3000/98/41	16,974	10,245	6,044	4,170
4000/83/47	22,632	13,660	8,059	5,560
5000/83/56	28,290	17,075	10,074	6,950

## Delivered Lumens

LED Module	Optic (Reflector)			
Lumens/CRI/Wattage	K1	W2	J3	W4
2000/83/21	1,454	1,175	1,472	1,139
2000/98/28	1,454	1,175	1,472	1,139
3000/83/32	2,180	1,763	2,208	1,709
3000/98/41	2,180	1,763	2,208	1,709
4000/83/47	2,907	2,351	2,944	2,279
5000/83/56	3,634	2,938	3,680	2,848

## Efficacy = Lumens Per Watt


LED Module	Optic (Reflector)			
Lumens/CRI/Wattage	K1	W2	J3	W4
2000/83/21	69	56	70	54
2000/98/28	52	42	53	41
3000/83/32	68	55	69	53
3000/98/41	53	43	54	42
4000/83/47	62	50	63	48
5000/83/56	65	52	66	51

*Absolute range of values are +/- 10% of typical value, and are for all color temperatures*


LED Module Lumens/CRI/Wattage Letter Code	2000/83/21 20-83	2000/98/28 20-98	3000/83/32 30-83	3000/98/41 30-98	4000/83/47 40-83	5000/83/56 50-83
Nominal Fixture Power (+/- 20%), Watts	21	28	32	41	47	56
Maximum Inrush Current Amps	10	10	10	10	10	10
Minimum Power Factor	0.92	0.92	0.92	0.92	0.92	0.92

*Inrush current is instantaneous current drawn by the LED only when fixture is initially powered on or instantaneously changed from full dim to full bright. For more details see Dimming Application Sheet, IS-0119.*


# LX2084 • OPTICS

**LX-K10-REF-CLR (K1)  
(111mm/10°)**


Faceted reflectively coated metal optic. Tool-less twist and lock installation. Aluminized finish.

**LX-W20-REF-CLR (W2)  
(72mm/20°)**

Faceted reflectively coated metal optic. Tool-less twist and lock installation. Aluminized finish.

**LX-J30-REF-CLR (J3)  
(111mm/30°)**

Faceted reflectively coated metal optic. Tool-less twist and lock installation. Aluminized finish.

**LX-W40-REF-CLR (W4)  
(72mm/40°)**

Faceted reflectively coated metal optic. Tool-less twist and lock installation. Aluminized finish.

LX2084

• PHOTOMETRIC DATA

LED RATING: 30-98

K1- 111mm DIA Optic	10°
Beam Spread (minimum)	16974
Center Beam Candlepower	98
CRI	
W2- 72mm DIA Optic	20°
Beam Spread (minimum)	10245
Center Beam Candlepower	98
CRI	
J3- 111mm DIA Optic	30°
Beam Spread (minimum)	6044
Center Beam Candlepower	98
CRI	
W4- 72mm DIA Optic	40°
Beam Spread (minimum)	4170
Center Beam Candlepower	98
CRI	

LED RATING: 50-83


K1- 111mm DIA Optic	10°
Beam Spread (minimum)	28290
Center Beam Candlepower	83
CRI	
W2- 72mm DIA Optic	20°
Beam Spread (minimum)	17075
Center Beam Candlepower	83
CRI	
J3- 111mm DIA Optic	30°
Beam Spread (minimum)	10074
Center Beam Candlepower	83
CRI	
W4- 72mm DIA Optic	40°
Beam Spread (minimum)	6950
Center Beam Candlepower	83
CRI	

LED RATING: 30-98

All Max. Footcandles at 0° Beam Axis

W4 (40°)	J3 (30°)	W2 (20°)	K1 (10°)
4170	6044	10245	16974
1043	1511	2561	4244
463	672	1138	1886
261	378	640	1061
167	242	410	679
116	168	285	472
85	123	209	346
65	94	160	265
51	75	126	210
42	60	102	170
34	50	85	140
29	42	71	118
25	36	61	100
21	31	52	87
19	27	46	75
16	24	40	66
14	21	35	59
13	19	32	52
12	17	28	47
10	15	26	42
9	14	23	38
9	12	21	35
8	11	19	32
7	10	18	29
7	10	16	27

All Distances in Feet




Photometric Data based on LED Rating: 30-98 (3000 Lumens/98CRI/41watts)

LED RATING: 50-83

All Max. Footcandles at 0° Beam Axis

W4 (40°)	J3 (30°)	W2 (20°)	K1 (10°)
6950	10074	17075	28290
1738	2519	4269	7073
772	1119	1897	3143
434	630	1067	1768
278	403	683	1132
193	280	474	786
142	206	348	577
109	157	267	442
86	124	211	349
70	101	171	283
57	83	141	234
48	70	119	196
41	60	101	167
35	51	87	144
31	45	76	126
27	39	67	111
24	35	59	98
21	31	53	87
19	28	47	78
17	25	43	71
16	23	39	64
14	21	35	58
13	19	32	53
12	17	30	49
11	16	27	45

All Distances in Feet



Photometric Data based on LED Rating: 50-83 (5000 Lumens/83CRI/56watts)

LX2084 • ACCESSORIES

A line drawing of a cylindrical metal hood. It has a circular top rim and a slightly flared bottom rim. A small circular detail is visible on the top rim.

## HOOD-EXT-LX84-NXB-X

Cylindrical metal hood controls spill light and glare. Does not include cross baffle.

Specify finish as follows:

HOOD-EXT-LX84-NXB-B (BLACK)

HOOD-EXT-LX84-NXB-W (WHITE)

HOOD-EXT-LX84-NXB-S (SILVER)

A line drawing of a cylindrical metal hood, similar to the one in the previous image, but with a cross baffle inside. The baffle is a rectangular frame with two diagonal bars forming an 'X' shape.

## HOOD-EXT-LX84-WXB-X

Cylindrical metal hood controls spill light and glare. Includes cross baffle.

Specify finish as follows:

HOOD-EXT-LX84-WXB-B (BLACK)

HOOD-EXT-LX84-WXB-W (WHITE)

HOOD-EXT-LX84-WXB-S (SILVER)

A line drawing showing three circular lenses. Two are overlapping, and one is in front of them. They have a textured, mesh-like appearance.

## SPREAD LENSES AND BEAM SOFTENER

No.	Description	% of Light Transmission
C990	Spread Lens/Clear	83 (5°X 50°)
C992	Spread Lens/Clear	85 (5°X 30°)
C995	Spread Lens/Clear	83 (50°X 50°)
C996	Spread Lens/Clear	86 (45°X 50°)
C998	Beam Softener/Clear	80 (45°X 45°)

A line drawing showing three circular mesh screens. Two are overlapping, and one is in front of them. They have a fine, grid-like texture.

## 1'LIGHT BLOCKING SCREENS C

Stainless steel mesh screens used alone or in combinations will block from approximately 20% to 90% of the transmitted light without changing color temperature of the light.

No.	% of Light Blocked
C801S	20
C802S	30
C803S	40

A line drawing of a circular louver. It has a black frame and a hexagonal mesh pattern in the center.

## LOUVER HEX CB

1/8" thick Hexcell black metal louver used for thin profile. Black finish.

A line drawing of a circular backer ring. It has a black frame and a central circular opening.

## BACKER RING CB

Aluminum ring to hold gel when no other size C accessories are being used. Black finish.

1. Figures vary based upon LED Module/Optic being used and relationship of screen(s) to LED Module/Optic and to each other.

# LX2084 • GELS

As the foremost innovator in accent lighting, LSI offers a complete range of pre-cut Gels to modify the spread and color of light for the LumeLEX LED Series.



## LumeLEX® SPREAD GELS

Size: C (121 mm diameter)	Spread Gel
GEL-L1-C	1° Spread Gel
GEL-L5-C	5° Spread Gel
GEL-L10-C	10° Spread Gel
GEL-L20-C	20° Spread Gel
GEL-L30-C	30° Spread Gel
GEL-L40-C	40° Spread Gel
GEL-L60-C	60° Spread Gel
GEL-L80-C	80° Spread Gel
GEL-L30X5-C	30° by 5° Spread Gel
GEL-L40X1-C	40° by 1° Spread Gel
GEL-L60X1-C	60° by 1° Spread Gel
GEL-L60X10-C	60° by 10° Spread Gel
GEL-L75X45-C	75° by 45° Spread Gel
GEL-L90X60-C	90° by 60° Spread Gel
GEL-R101-C	Beam Softener

## LumeLEX® COLOR GELS

Size: C (121 mm diameter)	Gel Color	% of Light Transmission	Size: C (121 mm diameter)	Gel Color	% of Light Transmission
GEL-R2-C	Bastard Amber	78	GEL-R312-C	Canary	85
GEL-R7-C	Pale Yellow	96	GEL-R331-C	Shell Pink	68
GEL-R12-C	Straw	88	GEL-R383-C	Sapphire Blue	4
GEL-R13-C	Straw Tint	78	GEL-R397-C	Pale Grey	70
GEL-R14-C	Medium Straw	68	GEL-R2001-C	Storaro Red	12
GEL-R21-C	Golden Amber	43	GEL-R2004-C	Storaro Green	15
GEL-R25-C	Orange Red	14	GEL-R2009-C	Storaro Violet	3
GEL-R26-C	Light Red	12	GEL-R3202-C	Full Blue	36
GEL-R27-C	Medium Red	4	GEL-R3204-C	Half Blue	52
GEL-R57-C	Lavender	24	GEL-R3206-C	Third Blue	64
GEL-R62-C	Booster Blue	54	GEL-R3216-C	Eighth Blue (Boosts 3200K to 3300K)	81
GEL-R71-C	Sea Blue	30	GEL-R3318-C	Tough 1/8 Minusgreen	89
GEL-R72-C	Azure Blue	44	GEL-R3410-C	Roscosun (1/8 CTO) (Reduces 5500K to 4900K)	92
GEL-R91-C	Primary Green	7	GEL-R3441-C	Full Straw (CTS)	50
GEL-R97-C	Light Grey	50	GEL-R3443-C	Quarter Straw (CTS)	81
GEL-R98-C	Medium Grey	25	GEL-R4330-C	CalColor 30 Cyan	63
GEL-R101-C	Light Frost	N/A	GEL-R4415-C	CalColor 15 Green	67
GEL-R104-C	Tough Silk	N/A	GEL-R4490-C	CalColor 90 Green	25
GEL-R119-C	Lt. Hamburg Frost	N/A	GEL-R4860-C	CalColor 60 Pink	46
GEL-R121-C	Blue Diffusion	N/A	GEL-R4890-C	CalColor 90 Pink	38
GEL-R305-C	Rose Gold	75	GEL-R4930-C	CalColor 30 Lavender	47

\* Backer Ring CB required to hold gels when no other rimmed "C" accessories are used.

LSI ROSCO GEL CCT CONVERSION CHART FROM 3000K			
Type	ROSCO #	ROSCO Description	Resulting CCT
Amber Filters Lower CCT	3420	Double CTO	1531
	3407	Sun CTO	1999
	3401	Sun 85	2154
	3411	Sun 3/4 CTO	2154
	3408	Sun 1/2 CTO	2414
	3409	Sun 1/4 CTO	2664
	3410	Sun 1/8 CTO	2830
	3114	UV Filter	2930
Blue Filters Raise CCT	3220	Double Blue	N/A
	3202	Full Blue	4942
	3203	Three-Quarter Blue	4286
	3204	Half Blue	3769
	3206	Third Blue	3517
	3208	Quarter Blue	3297
	3216	Eighth Blue	3112



# COLOR MEDIA

## COLOR FILTERS

As the foremost innovator in accent lighting, LSI offers a complete range of permanent fade-free glass color filters, which are available in four stock diameters. All glass color filters are rimmed in a seamless aluminum ring and are slotted for heat expansion.



Size	Diameter	LSI Fixture Series	No.	Color	1% of Light Transmission
AAA	2 3/8"	LumeLEX® 2020/2030/2031/2038, SSLCX16, SSL260	902	Medium Pink	36
AA	3"	LumeLEX® 2044, LumeLEX 2048	903	Deep Pink	37
A	3 1/2"	LumeLEX® 2060, SSL230, SSLCX30, SSLGR30CL	904	Flesh Pink	73
C	4 3/4"	LumeLEX® 2084, LumeLEX® 2088, SSL238, SSLCX36, SSLCX38, SSLGR38CL	906	Pale Lavender	14
			907	Surprise Pink	19
			908	Lilac	21
			910	Warm Red	10
			911	Strawberry	6
			912	Ruby	4
			913	Magenta	1
			914	Light Amethyst	25
			915	Medium Amethyst	16
			916	Deep Amethyst	4
			917	Olive	18
			918	Light Green	68
			920	Medium Green	25
			921	Deep Green	7
			922	Silver green	65
			923	Yellow Green	49
			924	Emerald Green	12
			925	Light Turquoise	68
			926	Medium Turquoise	40
			927	Deep Turquoise	17
			928	Light Blue	34
			930	Medium Blue	3
			932	Daylight	59
			933	Gene Moore Blue	18
			936	Grey	56
			937	Light Blue Green	17
			939	Light Amber	68
			940	Medium Amber	48
			941	Deep Amber	43
			942	Straw	78
			943	Gold	87
			944	Canary Yellow	84
			945	Lemon	81
			946	Pumpkin	32
			947	Tangerine	20
			948	Orange	23
			949	Pink Gold	54
			950	Bronze	48
			951	Brass	11
			952	Autumn Tan	11
			953	Leaf Brown	19
			954	Butter Pecan	3
			955	Toasted Almond	1

### Notes:

1. Values given are approximate due to slight variations in glass color and thickness.


# COLOR MEDIA

## DICHROIC COLOR FILTERS

In addition to our complete line of glass color filters, LSI now offers dichroic glass color filters that achieve purer, more saturated, richer color by selective wavelength transmission. Since these filters reflect rather than absorb the unwanted color wavelengths, a higher intensity of colored light can be obtained with fewer or lower wattage fixtures. In addition, this selective transmission allows for very accurate color matching from filter to filter.

All standard LSI filter sizes are available in a wide palette of well chosen dichroic colors that can be used with all LSI fixtures that accept accessories.

LSI dichroic glass color filters have the added benefit of being rimmed for extra durability to allow for frequent usage without fear of breakage or edge chipping.



Size	Diameter	LSI Fixture Series	Technical Data	No.	Color	% of Light Transmission
AAA	2 3/8"	LumeLEX® 2020/2030/2031/2038, SSLCX16, SSL260	Dichroic color filters are created in a vacuum chamber by multi-layer vapor deposits of different minerals onto low expansion, chemically resistant Borosilicate glass.	2001	Light Pink	69
AA	3"	LumeLEX® 2044, LumeLEX 2048	Deposits are made in alternating layers of varying microscopic thickness which allow very narrow color wavelengths to be selectively transmitted and all other wavelengths to be reflected.	2002	Medium Pink	43
A	3 1/2"	LumeLEX® 2060, SSL230, SSLCX30, SSLGR30CL	LSI does not recommend using dichroic color filters with lamps or fixtures that have beam spreads greater than 40° because a secondary color aura is created by the wide angular transmitted wavelengths that are different than the desired color wavelength.	2003	Hot Pink	11
C	4 3/4"	LumeLEX® 2084, LumeLEX® 2088, SSL238, SSLCX36, SSLCX38, SSLGR38CL	Since there is mainly transmission and reflection of the color wavelengths by the dichroic filter and very little absorption, the dichroic filter can be used with many high temperature lights that normally would not accept color filters.	2004	Pale Pink	55
				2010	Deep Magenta	29
				2011	Lavender	24
				2012	Vivid Magenta	31
				2013	Lavender Accent	48
				2014	Lilac	37
				2015	Purple Fusion	12
				2020	Sky Blue	39
				2021	Sea Blue	39
				2022	Cyan	33
				2023	Light Blue Green	30
				2024	Primary Blue	24
				2025	Medium Red Blue	15
				2026	Deep Purple	16
				2027	Peacock Blue	53
				2028	Mediterranean Blue	20
				2029	Boost Blue	51
				2040	Light Yellow Green	64
				2041	Fern Green	47
				2042	Turquoise	35
				2043	Primary Green	31
				2044	Industrial Green	64
				2050	Yellow	80
				2051	Amber	71
				2052	Amber Blush	38
				2053	Bastard Amber	71
				2054	Goldenrod	63
				2055	Bright Straw	56
				2060	Medium Orange	51
				2061	Orange	44
				2070	Flame Red	27
				2071	Primary Red	25